

MT2E CABIN SERIES

LS Tractor



MT235EC / MT235HEC / MT240HEC
VALUE COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT2E CABIN SERIES VALUE COMPACT TRACTORS

MT235EC / MT235HEC / MT240HEC



RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With An Abundance Of Standard Features



BACKHOE:
Excellent Capacity, Smooth And Consistent Operation For Added Control



ROTARY CUTTER:
Durable Heavy Steel Design Providing Quality And Strength



BOX BLADE:
Features A Heavy Welded Steel Design For Use In Demanding Applications

FEATURES

- 6 Year Warranty *
- 3 Range Two Pedal Hydrostatic Transmission
- 12F X12R Gear (MT235E Cab)
- Standard Mid-Mount Valve With Joystick
- Deluxe Suspension Seat With Armrest



Left And Right Cab Doors
Premium Seat Providing Access To Either Side Of The Cab



3 Range Hydrostatic Transmission
Provides Comfort And Excellent Controllability Of Tractor Movement



Standard Dual Mirrors
Provide Added Visibility



Standard Drawbar
Provides Value And Enables Trailering etc.



Ground Level Fueling
Provides Easy Access



Standard Grille Guard With Loader
Provides Added Protection



High-Capacity Loader
With High Lift Height And Standard Skid Steer Coupler



Standard Integrated Joystick
Mid Mount Valve, Providing Deluxe Fit And Finish



Electronic PTO
For Ease Of Use

SPECIFICATIONS

CATEGORY	MT235EC	MT235HEC	MT240HEC
ENGINE	MT235EC	MT235HEC	MT240HEC
Type	Vertical Water-Cooled 4Cycle Diesel Engine		
Model (Tier 4)	L3C19-T		
Engine HP (gross)	35	40	40
PTO (HP)	29.7	28	32
Rated Speed (rpm)	2600		
Displacement-cu (in ³)	114.7		
Fuel Tank Capacity (gal.)	12.4		
Alternator (V-A)	12 - 70		
DRIVE TRAIN			
Transmission	Synchro Shuttle	HST	
No. Of Speed	F12 x R12 (GEAR)	3 Ranges (HST)	
Brakes	Wet, Multi - Disc		
PTO			
Type	Independent		
Rear (rpm)	540		
Mid (rpm)	2000		
HYDRAULIC SYSTEM			
Control System	Position / Draft		
Implement Pump (gpm)	8.2		
Steering Pump (gpm)	4.1(GEAR)	5.5(HST)	
Steering	Hydrostatic Power Steering		
Total Flow (gpm)	12.3(GEAR)	13.7(HST)	
Category (3pt Hitch)	CAT I		
Hitch Lift Capacity (Hitch End) (lbs.)	1808		
Remote Valves	Option		
DIMENSION			
Overall Length (Frame To Link, in.)	128.3		
Overall Width With Tires (in.)	62		
Wheelbase (in.)	69		
Height To Top Of ROPS (in.)	86.6		
TIRE SIZE			
Front / Rear Ag	7 - 14 / 11.2 - 24		
Front / Rear Industrial	25 x 8.5 - 14 / 43 x 16 - 20		
Front / Rear Turf	25 x 8.5 - 14 / 41 x 14 - 20		
WEIGHT			
Total Weight w/o Ballast (lbs.)	3,589	3,655	3,661

*All Specs and features are subject to change, and pictures could include optional equipment etc.

* MT2E Cab Series Cab Models are not equipped with AC

FRONT END LOADER	LL3116
TRACTOR APPLICATION	ALL SERIES
Bucket Size (in.)	66 66
Maximum Lift Height (in.)	92.7 - 94.4
Clearance With Attachment Dump (in.)	61.7 - 64.4
Reach At Maximum Height (in.)	15 - 15.4
Maximum Dump Angle (deg.)	48 - 52
Maximum Rollback Angle (deg.)	43 - 41
Digging Depth (in.)	4.3
Overall Height In Carry Position (in.)	49.1 - 51.4
Lift Capacity (At Pivot Pin) (lbs.)	2,178 - 2,185
Breakout Force (At Pivot Pin) (lbs.)	3,450 - 3,612
Approx. Weight (Loader w/o Bucket) (lbs.)	717

BACKHOE	LB2104
TRACTOR APPLICATION	XR3 100 SERIES
Digging Depth (in.)	89.7
Reach From Centerline Of Swing Pivot (in.)	125.2
Loading Height (in.)	72.4
Swing Arc (deg.)	180
Transport Height (in.)	83.5
Bucket Rotating (deg.)	180
Stabilizer Spread (Down Position) (in.)	68.7
Stabilizer Spread (Up Position) (in.)	46.4
Bucket Digging Force (lbs.)	2,679

Additional/Optional Equipment

- Telescopic Lower Link
- Side Step - RH
- 7 Pole Connector
- Horn
- Sun Screen
- Interior Rear View Mirror
- External Position Lever
- Beacon Lamp
- Work Light
- Audio Assy-Without Bluetooth
- Audio Assy-Bluetooth
- Rear Wiper
- Mid PTO
- Remote Valve - 2Pair 1STD. 1Detent



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

