

MT3 (35/40) SERIES

LS Tractor



MT335H / MT335HC / MT340HC
PREMIUM COMPACT TRACTORS

6 YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT3 (35/40) SERIES

PREMIUM COMPACT TRACTORS


RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With
An Abundance Of
Standard Features



LAND GRADER:
Heavy Steel
Construction, High
Strength, Designed
For Use In Demanding
Applications



ROTARY CUTTER:
Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:
Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

- *6 Year Warranty*
- *Available In ROPS And Cab (ROPS Limited To MT335H)*
- *3 Range Hydrostatic Transmission (2 Pedal) With Linked Pedal*
- *High-Flow Implement Hydraulic Pump*
- *Premium Operator Platform And Cab*



**Front Hitch And
Sub-Frame Capable**
Allow For Front Implements



Dual Large Entry Doors
Provide Easy Access



Ground Level Fueling
Allow Easy Access For
Fueling



Standard Step
Provides Ease Of Access
To Platform



**3 Range Hydrostatic
Transmission, (2 Pedal)**
Comfortable And Efficient
Operator Control




Linked Pedal
Enables Throttle And Hydro
Pedal To "Link" Enabling
Efficient Engine Power Use



Spacious Cab
Provides Excellent Visibility



Integrated Joystick
Provides Operator Comfort



Standard Dual Mirrors
Enhances Visibility

MT335H / MT335HC / MT340HC



SPECIFICATIONS

CATEGORY			
ENGINE	MT335H	MT335HC	MT340HC
Type	3 Cylinder, Liquid-cooled, Diesel, TC, CRDI		
Model (Tier 4)	L3C19-T		
Engine HP (gross)	35		40
PTO (HP)	28		32
Rated Speed (rpm)	2,600		
Displacement (in ³ .)	114.7		
Fuel Tank Capacity (gal.)	12.4 (Cabin) / 10.6 (ROPS)		
Alternator V-A	12-70		
DRIVE TRAIN			
Transmission	Hydrostatic		
No. Of Speed	2 Pedal with 3 Range - HST		
Brakes	Wet, Multi-disc		
PTO			
Type	Independent		
Rear (rpm)	540		
Mid PTO (Option)	2,000		
HYDRAULIC SYSTEM			
Control System	Position & Draft		
Implement Pump (gpm)	8.2		
Steering Pump (gpm)	5.5		
Steering	Hydrostatic Power Steering		
Total Flow (gpm)	13.7		
Category (3pt Hitch)	CAT I		
Hitch Lift Capacity Hitch End (lbs.)	1,808		
Remote Valves	2 Pair		
DIMENSION			
Overall Length (Bumper To Link, in.)	128.3		
Overall Width With Tires (in.)	62		
Wheelbase (in.)	69		
Height To Top ROPS/Cab (in.)	94		86.6
TIRE SIZE			
Front / Rear Ag	7 - 14 / 11.2 - 24		
Front / Rear Industrial	25 x 8.5 - 14, 43 x 16 - 20		
Front / Rear Turf	25 x 8.5 - 14, 41 x 14 - 20		
WEIGHT			
Total Weight w/o Ballast (lbs.)	3,285	3,655	3,661

FRONT END LOADER		LL3116
TRACTOR APPLICATION	MT335/40 (Prev XR3100)	
Bucket Size (in.)	66	
Maximum Lift Height (in.)	94.4	
Clearance With Attachment Dump (in.)	64.4	
Reach At Maximum Height (in.)	15.4	
Maximum Dump Angle (deg.)	52	
Maximum Rollback Angle (deg.)	41	
Digging Depth (in.)	4.3	
Overall Height In Carry Position (in.)	51.4	
Lift Capacity (At Pivot Pin) (lbs.)	2,185	
Breakout Force (At Pivot Pin) (lbs.)	3,612	
Approx. Weight (Loader w/o Bucket) (lbs.)	717	

BACKHOE		LB2104
TRACTOR APPLICATION	MT335/40 (Prev XR3100)	
Digging Depth (in.)	89.8	
Reach From Centerline Of Swing Pivot (in.)	125.2	
Loading Height (in.)	72.4	
Swing Arc (deg.)	180	
Transport Height (in.)	83.5	
Bucket Rotating (deg.)	180	
Stabilizer Spread (Down Position) (in.)	68.7	
Stabilizer Spread (Up Position) (in.)	46.4	
Bucket Digging Force (lbs.)	2,673	

Additional Equipment

- Standard Rubber Floor Mat
- Standard Foldable ROPS (ROPS Models Only)
- Standard 2 Rear Remote Valves
- Optional 3rd Function

**All Specs and features are subject to change, and pictures could include optional equipment etc.*



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

